

Dräger Pac Series Single Gas Detectors

The Dräger Pac series is composed of fast, accurate, reliable and easy-to-use personal single gas detectors. The devices are extremely robust, featuring clear warning signals and language-free displays. Their cutting-edge sensor technology delivers reliable results every time.



INNOVATIVE DESIGN

Dräger Pac devices are small and portable, but packed with several innovations. The requirements for the various uses and applications in the industrial sector were carefully considered during their development.

ROBUST AND CLEAR

The impact-resistant and chemical-resistant rubber housing meets the requirements of IP 68 so that the devices can be exposed to spray water. A stable and rotating alligator clip ensures secure fastening to the clothing of the worker. Hi-Vis colored (yellow for H₂S) overlays help distinguish the gases monitored from a distance.

UNAMBIGUOUS RESULTS

The devices are easy to use with one hand even when wearing gloves and they continuously provide clear and unambiguous results. The large numeric LCD display is designed without text and has a backlight that ensures good readability even in the dark.

In addition to vibration and acoustic multi-tone alarms, the instruments emit an optical alarm signal clearly visible from any direction; the LEDs at the top and bottom of the unit flash brightly.

ADVANCED TECHNOLOGY

Equipped with the latest Dräger XXS miniature sensor technology, Dräger Pac series represents excellence in the field of gas detection. The devices are extremely durable, highly responsive, and have a variety of features for capturing events including the ability to adjust the frequency of functional tests and calibrations individually.

SAFETY FIRST

Maximum safety is ensured even when the device is carried in a pocket or a gas input is accidentally covered. The clever positioning of the sensor allows safe measurements both from above and in front of the device.



D-440-2009

Dräger Pac® 3500



D-537-2009

Dräger Pac® 5500



D-166205-2009

Dräger Pac® 7000

Key features of the Pac series



DRÄGER PAC® 3500

- Measures carbon monoxide, hydrogen sulfide, or oxygen
- Service life of 2 years
- Event logger for up to 60 events
- Warranty of 2 years
- Rapid functional tests on site



DRÄGER PAC® 5500

All advantages of the Dräger Pac 3500 plus:

- No limit to the service life of the device
- Service:
 - Easy to replace batteries and sensors
 - Replaceable dust and water filters
- Estimated sensor service life of 5-8 years



DRÄGER PAC® 7000

All advantages of the Dräger Pac 5500 plus:

- Measures carbon dioxide, sulfur dioxide, chlorine, hydrogen cyanide, ammonia, nitrogen dioxide, nitric oxide, phosphine, or organic vapors
- Optional 5 year warranty* for the H₂S, O₂, and CO devices
- Data logger for storage of gas concentrations and events with date and time
 - (120 hours at 1 record per minute)
- Configurable TWA and STEL alarms
- Recording maximum concentrations
- Automatic function test option

TESTS FOR YOUR SAFETY

The international guidelines OSHA - ISEA, IEC 60079-29-2, DIN EN60079-29-2 and BGI 512 836/BGI testing of gas detection and warning devices function tests and a known concentration of gas in certain specified intervals is required. These tests not only check whether the gas to be measured reaches the sensor through the dust

and water filter, they also test whether it is correctly calibrated and the alarms are set correctly and working properly.

The devices of the Pac series feature individually adjustable functional tests and calibration intervals. A warning symbol indicates when a functional test or calibration is required. Depending on the application, the

functional test and calibration may have to be carried out daily if the test was not completed successfully.

If the test is not carried out or if it fails, the device can automatically display an error message to inform the user that the device is not operational.

DRÄGER BUMP TEST STATION

The Dräger bump test station is available for the Dräger Pac series devices to carry out the functional tests quickly, easily and without a PC or additional power source.



D-47666-2012

CALIBRATION MADE EASY

Dräger X-dock® gives you full control over your Dräger portable gas detection instruments when regularly using a large number of Pac devices. Automatic bump tests and calibrations with reduced test gas consumption and short test duration save time and money. Extensive documentation and reports keep track of data.



D-47894-2012

ORDER INFORMATION

Pac 3500

Description	Measuring range	Alarm threshold A1/A2 (standard)	Resolution	Response time	Order number
Dräger Pac 3500 CO	0 – 500 ppm	35/50 ppm	1 ppm	15 sec.	45 43 957
Dräger Pac 3500 H ₂ S	0 – 100 ppm	10/15 ppm	0.1 ppm	15 sec.	45 43 958
Dräger Pac 3500 H ₂ S ¹⁾	0 – 100 ppm	10/15 ppm	0.1 ppm	15 sec.	45 43 963
Dräger Pac 3500 O ₂	0 – 25 Vol. %	19.5/23.5 Vol. %	0.1 Vol. %	10 sec.	45 43 959
Dräger Pac 3500 O ₂ ²⁾	0 – 25 Vol. %	19.5/23.5 Vol. %	0.1 Vol. %	10 sec.	45 43 964

Yellow colored overlays for H₂S devices, 10/Pack 83 20 978

Blue colored overlays for O₂ devices, 10/Pack 83 20 977

Pac 5500

Description	Measuring range	Alarm threshold A1/A2 (standard)	Resolution	Response time	Order number
Dräger Pac 5500 CO	0 – 500 ppm	35/50 ppm	1 ppm	15 sec.	45 43 960
Dräger Pac 5500 H ₂ S	0 – 100 ppm	10/15 ppm	0.1 ppm	15 sec.	45 43 961
Dräger Pac 5500 H ₂ S ¹⁾	0 – 100 ppm	10/15 ppm	0.1 ppm	15 sec.	45 43 965
Dräger Pac 5500 O ₂	0 – 25 Vol. %	19/23 Vol. %	0.1 Vol. %	10 sec.	45 43 962
Dräger Pac 5500 O ₂ ²⁾	0 – 25 Vol. %	19.5/23.5 Vol. %	0.1 Vol. %	10 sec.	45 43 966

Yellow colored overlays for H₂S devices, 10/Pack 83 20 978

Blue colored overlays for O₂ devices, 10/Pack 83 20 977

Pac 7000

Description	Measuring range	Alarm threshold A1/A2 (standard)	Resolution	Response time	Order number
Dräger Pac 7000 H ₂ S ¹⁾	0 – 100 ppm	10/20 ppm	1 ppm	15 sec.	83 18 674
Dräger Pac 7000 H ₂ S ²⁾	0 – 100 ppm	10/20 ppm	1 ppm	15 sec.	83 18 971
Dräger Pac 7000 H ₂ S	0 – 100 ppm	Customer request	1 ppm	15 sec.	83 18 677
Dräger Pac 7000 H ₂ S	0 – 100 ppm	10/20 ppm	0.1 ppm	15 sec.	83 21 004

Low concentration

Dräger Pac 7000 O ₂ ¹⁾	0 – 25 Vol. %	19/23 Vol. %	0.1 Vol. %	10 sec.	83 18 675
Dräger Pac 7000 O ₂ ²⁾	0 – 25 Vol. %	19.5/23.5 Vol. %	0.1 Vol. %	10 sec.	83 18 972
Dräger Pac 7000 O ₂	0 – 25 Vol. %	Customer request	0.1 Vol. %	10 sec.	83 18 678
Dräger Pac 7000 CO ¹⁾	0 – 1999 ppm	30/60 ppm	1 ppm	15 sec.	83 18 673
Dräger Pac 7000 CO ²⁾	0 – 1999 ppm	35/50 ppm	1 ppm	15 sec.	83 18 970
Dräger Pac 7000 Cl ₂	0 – 20 ppm	0.5/1.0 ppm	0.05 ppm	30 sec.	83 18 978
Dräger Pac 7000 HCN	0 – 50 ppm	2.5/4.5 ppm	0.1 ppm	15 sec.	83 18 973

¹⁾ Standard configuration Europa

²⁾ Standard configuration North America

ORDER INFORMATION CONTINUED

Dräger Pac 7000 NH ₃	0 – 300 ppm	25/50 ppm	1 ppm	20 sec.	83 18 979
Dräger Pac 7000 NO ₂	0 – 50 ppm	2.5/5.0 ppm	0.1 ppm	15 sec.	83 18 977
Dräger Pac 7000 NO	0 – 200 ppm	2.5/5.0 ppm	1 ppm	15 sec.	83 21 263
Dräger Pac 7000 PH ₃	0 – 20 ppm	0.1/0.2 ppm	0.01 ppm	10 sec.	83 18 974
Dräger Pac 7000 OV	0 – 200 ppm	5/10 ppm	0.5 ppm	100 sec.	83 21 006
Dräger Pac 7000 OV-A	0 – 200 ppm	5/10 ppm	1 ppm	100 sec.	83 21 007

5-year warranty (excl. filter and battery)

Dräger Pac 7000 5Y H ₂ S	0 – 100 ppm	10/20 ppm	1 ppm	15 sec.	83 21 032
Dräger Pac 7000 5Y O ₂	0 – 25 Vol. %	19.5/23.5 Vol. %	0.1 Vol. %	10 sec.	83 21 033
Dräger Pac 7000 5Y CO	0 – 1999 ppm	35/50 ppm	1 ppm	15 sec.	83 21 031

ACCESSORIES FOR THE DRÄGER PAC SERIES

Leather carrying case	45 43 822
-----------------------	-----------

Communication accessories

Dräger CC-Vision Basic, free at www.draeger.com	
Communication module, incl. USB cable	83 18 587

Calibration accessories

Calibration adapter	83 18 588
Dräger X-Dock 5300 Pac	83 21 881
Dräger bump test station for Dräger Pac, order gas separately	83 17 410

Spare parts

Lithium battery	45 88 183
Sensor filter (4 pcs.)	45 43 836

*on the electronics, with the exception of the battery

CORPORATE HEADQUARTERS

Drägerwerk AG & Co. KGaA
Moislinger Allee 53–55
23558 Lübeck, Germany

www.draeger.com

CANADA

Draeger Safety Canada Ltd.
7555 Danbro Crescent
Mississauga,
Ontario L5N 6P9
Tel +1 905 821 8988
Fax +1 905 821 2565

Customer Service
Tel 877 372 4371
Fax 800 329 8823

MEXICO

Draeger Safety S.A. de C.V.
German Centre
Av. Santa Fe, 170 5-4-14
Col. Lomas de Santa Fe
01210 México D.F.
Tel +52 442 246-1113
Fax +52 442 246-1114

Customer Service
Tel 800 723 3891

REGION CENTRAL

AND SOUTH AMERICA
Dräger Panama S. de R.L.
Complejo Business Park,
V tower, 10th floor
Panama City
Tel +507 377-9100
Fax +507 377-9130
contactcsa@draeger.com

USA

Draeger Safety, Inc.
101 Technology Drive
Pittsburgh, PA 15275
Tel +1 412 787 8383
Fax +1 412 787 2207

Customer Service
Tel 800 858 1737
Fax 800 922 5519

Technical Service
Tel 888 794 3806
Fax 888 794 3807

Manufacturer:

Dräger Safety AG & Co. KGaA
Revalstraße 1
23560 Lübeck, Germany